



TemplateMonster.com  
DELIVERING THE BEST TEMPLATES ON THE NET!

TemplateMonster.com

# WebAPI Specification

Web API User Guide

A complete guide to TemplateMonster.com WebAPI provides the documentation to realize the full potential of WebAPI (Web Application Programming Interface) and covers all aspects of retrieving information about TemplateMonster.com products.

---

# Table of Contents

---

|   |    |
|---|----|
| 1. Basic concepts .....                             | 1  |
| 2. Specification .....                              | 2  |
| 1. Accessing TemplateMonster Catalog via HTTP ..... | 2  |
| 1.1. templates_screenshots4.php .....               | 2  |
| 1.2. template_sources.php .....                     | 5  |
| 1.3. template_keywords.php .....                    | 6  |
| 1.4. authors.php .....                              | 7  |
| 1.5. categories.php .....                           | 8  |
| 1.6. styles.php .....                               | 9  |
| 1.7. template_categories.php .....                  | 10 |
| 1.8. template_styles.php .....                      | 11 |
| 1.9. featured.php .....                             | 12 |
| 1.10. template_info3.php .....                      | 13 |
| 1.11. currency.php .....                            | 15 |
| 2. Obtaining Screenshots. ....                      | 16 |
| 3. Checking an Order Status. ....                   | 16 |
| 4. XML API specification. ....                      | 17 |
| 4.1. t_info.zip. ....                               | 17 |
| 4.2. template_updates.php. ....                     | 22 |
| 4.3. template_xml.php. ....                         | 24 |
| 4.4. t_info_dir.zip. ....                           | 24 |
| 3. Versions History .....                           | 26 |
| 4. Appendix. ....                                   | 28 |
| 1. Useful Links. ....                               | 28 |
| 2. Links to the Shopping Cart .....                 | 28 |
| 3. Links to Templatetuning.com .....                | 29 |

---

# Chapter 1. Basic concepts

WebAPI is a set of scripts for retrieving information about templates from TemplateMonster.com's database. It is used to get this info and store it in your own database in any form for creating your customizable template shops. It is an excellent tool for those who know a web programming language such as PHP, ASP, Perl, Coldfusion, etc. It allows a total customization of TemplateMonster.com's affiliate program - you can download all the information, screenshots, etc. to your web server and manipulate all the data in any way you please.

There are many advantages of using the WebAPI. Here's a short list of them:

- Faster, because you don't have to keep calling to TemplateMonster's servers for info.
- Easier to show the information you want your clients to view.
- The ability to have a complete control over all of the data available on TemplateMonster.com.

Data stored on your own server don't depend on TemplateMonster.com's server load and temporary traffic problems, and the most important is that you can create your custom template shop design and implement many unique features like custom search engine, etc.

Your WebAPI based template shop can be implemented in 2 ways: you can store information about templates only or all templates' data. Storing information about templates only method includes storing information about template screenshots, sources available for a particular template, keywords that describe templates, author of the template, category and style the template belongs to, templates with "featured" status assigned, etc but screenshots and flash previews of the templates are stored on the remote server [www.template-help.com](http://www.template-help.com).

Storing all the templates' data implies storing all screenshots and flash previews of the templates which requires approximately 5 GB of server space besides storing information about templates.

WebAPI scripts for getting information about templates should be invoked at least once per 24 hours. The best time to invoke them is about 8.00 AM EST. Currency rate script (`currency.php`) should be invoked once per hour.

---

# Chapter 2. Specification

## 1. Accessing TemplateMonster Catalog via HTTP

### 1.1. templates\_screenshots4.php

**URL:**

[http://www.templatemonster.com/webapi/templates\\_screenshots4.php](http://www.templatemonster.com/webapi/templates_screenshots4.php)

**Description:**

Returns a plain text table of properties of selected templates.

**Status:**

0.2

**Synopsis:**

```
http://www.templatemonster.com/webapi/templates_screenshots4.php?[linebreak=<linebreak>]
[&delim=<delimiter>] [(&from=<first_template_number>&to=<last_template_number> | &last_added=Yes
| &sold=Yes)] [&filter=<filter_number>] [&category=<category_number>] [&keywords=<keywords>]
[&sort_by=<sort_type>] [&order=( asc | desc )] [&list_delim=<delimiter>] [&list_begin=<list_begin_char>]
[&list_end=<list_end_char>] [&full_path=<full_path_flag>][&currency=<currency>]
```

**Parameters:**

| Parameter      | Type    | Description  |
|----------------|---------|--|
| linebreak      | string  | a sequence of characters used to separate lines (default: \r\n)  |
| delim          | string  | a sequence of characters used to separate columns (default: \t)  |
| from           | integer | a starting template number (inclusive, default: 1)   |
| to             | integer | an ending template number (inclusive, default: a maximum item number available)  |
| last_added=Yes | string  | Templates from the last 'new templates report' will be listed only if this parameter exists and has a nonzero length.  |
| sold=Yes       | string  | Sold and permanently removed from TemplateMonster templates will be listed only if this parameter exists and has a nonzero length.   |
| filter         | integer | If this parameter exists, not all templates will be returned, but the ones that match certain criteria (default: 0). Acceptable values: <ul style="list-style-type: none"><li>• 0 - all templates except adult website templates</li><li>• 1 - website templates only (hosting website templates included)</li></ul> |

| Parameter            | Type    | Description   |
|----------------------|---------|---|
|                      |         | <ul style="list-style-type: none"> <li>• 2 - hosting website templates only</li> <li>• 3 - flash intro templates only</li> <li>• 4 - adult website templates only</li> <li>• 5 - unique logo templates only</li> <li>• 6 - non unique logo templates only</li> <li>• 7 - unique corporate identity packages only</li> <li>• 8 - non-unique corporate identity packages only.</li> </ul> |
| keywords             | string  | A space separated list of keywords associated with the template. If this parameter exists, not all templates will be returned but the ones that contain given keywords only.  |
| category             | integer | If this parameter exists, not all templates will be returned, but the ones that belong to this category only. Use a script categories.php to obtain acceptable values.  |
| sort_by              | string  | If this parameter exists, records will be sorted by a certain attribute. By default, records are sorted by a template number. Acceptable values: <ul style="list-style-type: none"> <li>• <i>number</i> - sort by a template number</li> <li>• <i>date</i> - sort by date of addition</li> <li>• <i>price</i> - sort by price</li> </ul>  |
| order=( asc   desc ) | string  | The default order is ascending. Acceptable values: <ul style="list-style-type: none"> <li>• <i>asc</i> - ascending order</li> <li>• <i>desc</i> - descending order</li> </ul>   |
| list_delim           | string  | a sequence of characters used to separate list items (default: , )  |
| list_begin           | string  | a sequence of characters used to mark the beginning of the list (default: { )   |
| list_end             | string  | a sequence of characters used to mark the end of the list (default: } )   |
| full_path            | string  | if this parameter exists and its value is 'true' a full path to screenshots is returned.  |

| Parameter | Type    | Description  |
|-----------|---------|--|
| currency  | 3 chars | <p>If this parameter exists templates prices will be priced using a currency different from USD. Acceptable values:</p> <ul style="list-style-type: none"> <li>• <i>EUR</i> - templates prices will be in Euros</li> <li>• <i>CAD</i> - templates prices will be in Canadian Dollars</li> <li>• <i>GBP</i> - templates prices will be in British Pounds Sterling</li> <li>• <i>JPY</i> - templates prices will be in Japanese Yen</li> <li>• <i>AUD</i> - templates prices will be in Australian Dollars.</li> </ul> |

**Response:**

Response is a plain text table delimited with <delimiter>. It consists of the following columns (without columns headers):

| Column                  | Type                 | Description  |
|-------------------------|----------------------|--|
| id                      | integer              | an item number of the template   |
| price                   | integer              | a regular price of the template  |
| exclusive price         | integer              | an exclusive price of the template   |
| date of addition        | date                 | the date when the template was added to the database in YYYY-MM-DD format                                  |
| number of downloads     | integer              | the number of downloads  |
| is hosting              | integer (1/0) 1-true | equals 1 for Hosting Website templates   |
| is flash                | integer (1/0) 1-true | equals 1 for Flash Intro templates   |
| is adult                | integer (1/0) 1-true | equals 1 for Adult templates   |
| is unique logo          | integer (1/0) 1-true | equals 1 for unique Logo templates   |
| is non unique logo      | integer (1/0) 1-true | equals 1 for non-unique Logo templates   |
| is unique corporate     | integer (1/0) 1-true | equals 1 for unique Corporate Identity Packages  |
| is non unique corporate | integer (1/0) 1-true | equals 1 for non-unique Corporate Identity Packages  |
| author's ID             | integer              | a template's author identifier   |
| is full site template   | integer (1/0) 1-true | equals 1 for Full Site templates   |
| number of pages         | integer              | the number of subpages (some templates are not full site templates but still contain several subpages).    |
| screenshots list        | list                 | a list of all screenshots of this template delimited with <delimiter>, started with <list_begin> and ended |

| Column | Type | Description  |
|--------|------|--|
|        |      | with <list_end>. By default, only variable part of URL is displayed. If you want to obtain a full URL, set <full_path> parameter to 'true' |

**Response example:**

`http://www.templatemonster.com/webapi/templates_screenshots4.php?delim=&from=12&to=30&keyword=hosting&sort_by=price&currency=EUR`

```
19|10.59|174.74|2002-05-01|5|0|0|0|0|0|0|1|0|0|{0/19-b.jpg,0/19-h.jpg,0/19-m.jpg,0/19-rs.jpg}| 25|12.36|144.73|
2002-05-01|5|0|0|0|0|0|0|1|0|0|{0/25-b.jpg,0/25-h.jpg,0/25-m.jpg,0/25-rs.jpg}| 12|13.24|138.55|2002-05-01|5|
0|0|0|0|0|1|0|0|{0/12-b.jpg,0/12-h.jpg,0/12-m.jpg}| 13|13.24|138.55|2002-05-01|9|0|0|0|0|0|1|0|0|{0/13-
b.jpg,0/13-h.jpg,0/13-m.jpg}| 15|13.24|112.08|2002-05-01|4|0|0|0|0|0|0|1|0|0|{0/15-b.jpg,0/15-h.jpg,0/15-m.jpg}|
17|13.24|181.80|2002-05-01|8|0|0|0|0|0|0|1|0|0|{0/17-b.jpg,0/17-h.jpg,0/17-m.jpg}| 27|13.24|131.49|
2002-05-01|5|0|0|0|0|0|0|1|0|0|{0/27-b.jpg,0/27-h.jpg,0/27-m.jpg,0/27-rs.jpg}| 21|15.00|157.97|2002-05-01|6|0|
0|0|0|0|0|1|0|0|{0/21-b.jpg,0/21-h.jpg,0/21-m.jpg,0/21-rs.jpg}| 29|15.00|122.67|2002-05-01|5|0|0|0|0|0|0|1|0|0|
{0/29-b.jpg,0/29-h.jpg,0/29-m.jpg,0/29-rs.jpg}| 18|17.65|166.79|2002-05-01|3|0|0|0|0|0|0|1|0|0|{0/18-b.jpg,0/18-
h.jpg,0/18-m.jpg,0/18-rs.jpg}| 23|21.18|184.44|2002-05-01|5|0|0|0|0|0|0|1|0|0|{0/23-b.jpg,0/23-h.jpg,0/23-
m.jpg,0/23-rs.jpg}| 26|21.18|215.33|2002-05-01|4|0|0|0|0|0|0|1|0|0|{0/26-b.jpg,0/26-h.jpg,0/26-m.jpg,0/26-
rs.jpg}| 16|25.59|157.97|2002-05-01|4|0|0|0|0|0|0|1|0|0|{0/16-b.jpg,0/16-h.jpg,0/16-m.jpg}| 28|25.59|224.16|
2002-05-01|5|0|0|0|0|0|0|1|0|0|{0/28-b.jpg,0/28-h.jpg,0/28-m.jpg}|
```

## 1.2. template\_sources.php

**URL:**

`http://www.templatemonster.com/webapi/template_sources.php`

**Description:**

Returns a plain text table of sources available for templates

**Status:**

0.1

**Synopsis:**

`http://www.templatemonster.com/webapi/template_sources.php?[[linebreak=<linebreak>]][&delim=<delimiter>][&from=<first_template_number>&to=<last_template_number>]`

**Parameters:**

| Parameter | Type    | Description   |
|-----------|---------|---|
| linebreak | string  | a sequence of characters used to separate the lines (default: \r\n)                       |
| delim     | string  | a sequence of characters used to separate the columns (default: \t)                       |
| from      | integer | an item number of the first template (inclusive, default: 1)                              |
| to        | integer | an item number of the last template (inclusive, default: a maximum item number available) |

**Response:**

Response is a plain text table delimited with <delimiter>. The table contains information about available sources for templates from <first\_template\_number> to <last\_template\_number> (inclusive). It consists of the following columns (without columns headers):

| Column  | Type    |
|---------|---------|
| id      | integer |
| sources | string  |

**Response example:**

*http://www.templatemonster.com/webapi/template\_sources.php?from=8888&to=8899*

```
8888      .PSD; .HTML;
8889      .FLA; .SWF; .PSD; .HTML;
8890      .FLA; .SWF; .PSD; .HTML;
8891      .PSD; .HTML; .FLA; .SWF;
8892      .PSD; .SWF; .FLA; .HTML;
8893      .FLA; .SWF; .PSD; .HTML;
8894      .FLA; .SWF; .PSD; .HTML;
8895      .SWF; .FLA; .PSD; .HTML;
8896      .PSD; .HTML;
8897      .PSD; .HTML;
8898      .PSD; .HTML;
8899      .FLA; .SWF; .PSD; .HTML;
```

## 1.3. template\_keywords.php

**URL:**

http://www.templatemonster.com/webapi/template\_keywords.php

**Description:**

Returns a plain text table of keywords associated with templates

**Status:**

0.1

**Synopsis:**

http://www.templatemonster.com/webapi/template\_keywords.php?[linebreak=<linebreak>][&delim=<delimiter>]  
[&from=<first\_template\_number>&to=<last\_template\_number>]

**Parameters:**

| Parameter | Type    | Description   |
|-----------|---------|---|
| linebreak | string  | a sequence of characters used to separate the lines (default: \r\n)                       |
| delim     | string  | a sequence of characters used to separate the columns (default: \t)                       |
| from      | integer | an item number of the first template (inclusive, default: 1)                              |
| to        | integer | an item number of the last template (inclusive, default: a maximum item number available) |

**Response:**



Response is a plain text table delimited with <delimiter>. The table contains information about keywords associated with templates from <first\_template\_number> to <last\_template\_number> (inclusive). It consists of the following columns (without columns headers):

| Column   | Type                                     |
|----------|--|
| id       | integer                                  |
| keywords | a string of keywords separated by spaces |

**Response example:**

[http://www.templatemonster.com/webapi/template\\_keywords.php?from=900&to=915](http://www.templatemonster.com/webapi/template_keywords.php?from=900&to=915)

```
900|music mp3 songs singers bands audio
901|cars driving speed highway road automobiles vehicles
902|creative webdesign webpage website butterfly
903|hosting servers traffic domain bandwidth notebook
905|mobile phones cellular communication communications phone
908|furniture company interior design studio
909|computers it computer retailer internet media communication communications
910|bank banking insurance credit credits finance financing stock exchange money
911|hosting servers traffic domain bandwidth
912|flash intro business
914|internet auction bids vendue clocks
915|domain registration domain name web address web hosting hosting host
```

## 1.4. authors.php

**URL:**

<http://www.templatemonster.com/webapi/authors.php>

**Description:**

Returns a plain text table of all authors' IDs and nicknames.

**Status:**

0.1

**Synopsis:**

[http://www.templatemonster.com/webapi/authors.php?\[\linebreak=<linebreak>\]\[&delim=<delimiter>\]](http://www.templatemonster.com/webapi/authors.php?[\linebreak=<linebreak>][&delim=<delimiter>])

**Parameters:**

| Parameter | Type   | Description   |
|-----------|--------|---|
| linebreak | string | a sequence of characters used to separate the lines (default: \r\n) |
| delim     | string | a sequence of characters used to separate the columns (default: \t) |

**Response:**

Response is a plain text table delimited with <delimiter>. The table contains information about the authors. It consists of the following columns (without columns headers):

| Column      | Type    |
|-------------|---------|
| author's ID | integer |

| Column            | Type   |
|-------------------|--------|
| author's nickname | string |

**Response example:**

[http://www.templatemonster.com/webapi/authors.php?delim=|](http://www.templatemonster.com/webapi/authors.php?delim=)

```

1|Big mama
3|Engine
4|MariArti
5|Casher
10|Dipixel
12|MAN!AK
13|Pharaoh
14|Dan
15|SR
17|Sloth
18|Bullet
19|Orange
21|Mc Oyed
22|Hummingbird
24|Wolf
25|Photographer
26|Shrew
27|Dgan Dgan
30|Glasgo Ranger
32|Flayer
36|Co-casher
37|Mr. Corpuscle

```

## 1.5. categories.php

**URL:**

<http://www.templatemonster.com/webapi/categories.php>

**Description:**

Returns a table of all templates categories

**Status:**

0.2

**Synopsis:**

[http://www.templatemonster.com/webapi/categories.php?\[/linebreak=<linebreak>\]\[&delim=<delimiter>\]\[locale=<locale>\]](http://www.templatemonster.com/webapi/categories.php?[/linebreak=<linebreak>][&delim=<delimiter>][locale=<locale>])

**Parameters:**

| Parameter | Type   | Description  |
|-----------|--------|--|
| linebreak | string | a sequence of characters used to separate the lines (default: \r\n)  |
| delim     | string | a sequence of characters used to separate the columns (default: \t)  |
| locale    | string | 2 characters on locales name (default: en) Acceptable values: <ul style="list-style-type: none"> <li>• cz - Czech</li> </ul> |

| Parameter | Type | Description   |
|-----------|------|---|
|           |      | <ul style="list-style-type: none"> <li>• <i>en</i> - English</li> <li>• <i>de</i> - German</li> <li>• <i>dk</i> - Danish</li> <li>• <i>du</i> - Dutch</li> <li>• <i>es</i> - Spanish</li> <li>• <i>fi</i> - Finnish</li> <li>• <i>fr</i> - French</li> <li>• <i>hu</i> - Hungarian</li> <li>• <i>it</i> - Italian</li> <li>• <i>pl</i> - Polish</li> <li>• <i>pt</i> - Portuguese</li> <li>• <i>ro</i> - Romanian</li> <li>• <i>tr</i> - Turkish</li> </ul> |

**Response:**

Response is a plain text table delimited with <delimiter>. The table contains information about templates categories. It consists of the following columns (without columns headers):

| Column           | Type    |
|------------------|---------|
| id of category   | integer |
| name of category | string  |

**Response example:**

<http://www.templatemonster.com/webapi/categories.php?locale=de&delim=>

```

1|Beauty
2|Business
3|Computer
4|Immobilien
5|Portal
6|Internet
7|Familie
8|Webdesign
9|Unterhaltung
10|Medizin
11|Auto
13|Neutral
14|Sport
16|Industrie
17|Religion
18|Medien
19|Musik

```

**1.6. styles.php**

**URL:**

<http://www.templatemonster.com/webapi/styles.php>

**Description:**

Returns a table of all templates styles

**Status:**

0.1

**Synopsis:**

[http://www.templatemonster.com/webapi/styles.php?\[\[linebreak=<linebreak>\]\]\[&delim=<delimiter>\]](http://www.templatemonster.com/webapi/styles.php?[[linebreak=<linebreak>]][&delim=<delimiter>])

**Parameters:**

| Parameter | Type   | Description   |
|-----------|--------|---|
| linebreak | string | a sequence of characters used to separate the lines (default: \r\n) |
| delim     | string | a sequence of characters used to separate the columns (default: \t) |

**Response:**

Response is a plain text table delimited with <delimiter>. The table contains information about templates styles. It consists of the following columns (without columns headers):

| Column        | Type    |
|---------------|---------|
| id of style   | integer |
| name of style | string  |

**Response example:**

[http://www.templatemonster.com/webapi/styles.php?delim=|](http://www.templatemonster.com/webapi/styles.php?delim=)

```
1|3d
2|Artworks
3|Cartoon
4|Clean
5|Collage
6|Dark
7|Futurist
8|Geometric
9|Grunge
10|Minimalist
11|Paper Made
12|Retro
13|Corporate
14|Urban / Street
15|Vector
16|Neutral
```

## 1.7. template\_categories.php

**URL:**

[http://www.templatemonster.com/webapi/template\\_categories.php](http://www.templatemonster.com/webapi/template_categories.php)

**Description:**

Returns a plain text table that is a sequence of templates numbers and corresponding categories names. Warning: a template can belong to many categories, so more than one line can contain this template id.

**Status:**

0.1

**Synopsis:**

`http://www.templatemonster.com/webapi/template_categories.php?[linebreak=<linebreak>][&delim=<delimiter>][&from=<first_template_number>&to=<last_template_number>]`

**Parameters:**

| Parameter | Type    | Description  |
|-----------|---------|--|
| linebreak | string  | a sequence of characters used to separate the lines (default: <code>\r\n</code> )  |
| delim     | string  | a sequence of characters used to separate the columns (default: <code>\t</code> )  |
| from      | integer | an item number of the first template (inclusive, default: 1)   |
| to        | integer | an item number of the last template (inclusive, default: a maximum item number available at <code>templatemonster.com</code> ) |

**Response:**

Response is a plain text table delimited with `<delimiter>`. The table contains information about categories content for templates from `<first_template_number>` to `<last_template_number>` (inclusive). It consists of the following columns (without columns headers):

| Column         | Type    |
|----------------|---------|
| id of template | integer |
| id of category | integer |

**Response example:**

`http://www.templatemonster.com/webapi/template_categories.php?delim=|&from=9005&to=9008`

```
9005 | 42
9005 | 50
9005 | 63
9005 | 83
9005 | 84
9006 | 42
9006 | 50
9006 | 63
9006 | 83
9006 | 84
9007 | 40
9007 | 66
9007 | 68
9008 | 27
9008 | 68
```

## 1.8. template\_styles.php

**URL:**

[http://www.templatemonster.com/webapi/template\\_styles.php](http://www.templatemonster.com/webapi/template_styles.php)

**Description:**

Returns a plain text table that is a sequence of templates numbers and corresponding styles IDs. Warning: a template can belong to many styles, so more than one line can contain this template id.

**Status:**

0.1

**Synopsis:**

[http://www.templatemonster.com/webapi/template\\_styles.php?\[\[linebreak=<linebreak>\]\]\[&delim=<delimiter>\]\[&from=<first\\_template\\_number>&to=<last\\_template\\_number>\]](http://www.templatemonster.com/webapi/template_styles.php?[[linebreak=<linebreak>]][&delim=<delimiter>][&from=<first_template_number>&to=<last_template_number>])

**Parameters:**

| Parameter | Type    | Description  |
|-----------|---------|--|
| linebreak | string  | a sequence of characters used to separate the lines (default: \r\n)  |
| delim     | string  | a sequence of characters used to separate the columns (default: \t)  |
| from      | integer | an item number of the first template (inclusive, default: 1)   |
| to        | integer | an item number of the last template (inclusive, default: a maximum item number available at templatemonster.com) |

**Response:**

Response is a plain text table delimited with <delimiter>. The table contains information about styles content for templates from <first\_template\_number> to <last\_template\_number> (inclusive). It consists of the following columns (without columns headers):

| Column         | Type    |
|----------------|---------|
| id of template | integer |
| id of style    | integer |

**Response example:**

[http://www.templatemonster.com/webapi/template\\_styles.php?delim=|&from=9002&to=9008](http://www.templatemonster.com/webapi/template_styles.php?delim=|&from=9002&to=9008)

```
9002 | 5
9003 | 2
9003 | 5
9003 | 16
9004 | 16
9005 | 4
9005 | 16
9006 | 4
9007 | 5
9007 | 9
9008 | 16
```

## 1.9. featured.php

**URL:**

<http://www.templatemonster.com/webapi/featured.php>

**Description:**

Returns a list of the numbers of featured templates. There are two types of featured templates: featured website templates and featured flash intro templates. You can review featured website templates at <http://www.templatemonster.com/index.php> and featured flash intro templates at <http://www.templatemonster.com/flash-templates.php>

**Status:**

0.1

**Synopsis:**

[http://www.templatemonster.com/webapi/featured.php?\[\[linebreak=<linebreak>\]\]\[&delim=<delimiter>\] \[&type=\( website | flash \)\]](http://www.templatemonster.com/webapi/featured.php?[[linebreak=<linebreak>]][&delim=<delimiter>] [&type=( website | flash )])

**Parameters:**

| Parameter | Type   | Description  |
|-----------|--------|--|
| linebreak | string | a sequence of characters used to separate the lines (default: \r\n)                              |
| delim     | string | a sequence of characters used to separate the columns (default: \t)                              |
| type      | string | a type of featured templates. Acceptable values: website or flash. The default value is website. |

**Response:**

Response is a plain text string containing template numbers delimited with <delimiter>.

**Response example:**

<http://www.templatemonster.com/webapi/featured.php?delim=|&type=flash>

9634 | 9426 | 8669 | 9635

## 1.10. template\_info3.php

**URL:**

[http://www.templatemonster.com/webapi/template\\_info3.php](http://www.templatemonster.com/webapi/template_info3.php)

**Description:**

Returns the info about the selected template.

**Status:**

0.2

**Synopsis:**

[http://www.templatemonster.com/webapi/template\\_info3.php?\[\[linebreak=<linebreak>\]\]\[&delim=<delimiter>\]\[&template\\_number=<template\\_number>\] \[&list\\_delim=<delimiter>\] \[&list\\_begin=<list\\_begin\\_char>\]\[&list\\_end=<list\\_end\\_char>\]](http://www.templatemonster.com/webapi/template_info3.php?[[linebreak=<linebreak>]][&delim=<delimiter>][&template_number=<template_number>] [&list_delim=<delimiter>] [&list_begin=<list_begin_char>][&list_end=<list_end_char>])

**Parameters:**

| Parameter       | Type    | Description   |
|-----------------|---------|---|
| linebreak       | string  | a sequence of characters used to separate the lines (default: \r\n)           |
| delim           | string  | a sequence of characters used to separate the columns (default: \t)           |
| template_number | integer | an item number of the template (default: 1)                                   |
| list_delim      | string  | a sequence of characters used to separate list items (default: , )            |
| list_begin      | string  | a sequence of characters used to mark the beginning of the list (default: { ) |
| list_end        | string  | a sequence of characters used to mark the end of the list (default: } )       |

**Response:**

Response is a plain text table delimited with <delimiter>. It consists of the following columns (without columns headers):

| Column                  | Type                 | Description  |
|-------------------------|----------------------|--|
| id                      | integer              | an item number of the template   |
| price                   | integer              | a template price (in USD)  |
| exclusive price         | integer              | an exclusive price of the template (in USD)  |
| date of addition        | date                 | date of addition in YYYY-MM-DD format  |
| number of downloads     | integer              | the number of downloads  |
| is hosting              | integer (1/0) 1-true | 1 for Hosting Website templates  |
| is flash                | integer (1/0) 1-true | 1 for Flash Intro templates  |
| is adult                | integer (1/0) 1-true | 1 for Adult templates  |
| is unique logo          | integer (1/0) 1-true | 1 for unique Logo templates  |
| is non unique logo      | integer (1/0) 1-true | 1 for non-unique Logo templates  |
| is unique corporate     | integer (1/0) 1-true | 1 for unique Corporate Identity Packages   |
| is non unique corporate | integer (1/0) 1-true | 1 for non-unique Corporate Identity Packages   |
| author's ID             | integer              | a template's author identifier   |
| author's nick           | string               | a template's author nickname   |
| is full site template   | integer (1/0) 1-true | 1 for Full Site templates  |
| is Real Size            | integer (1/0) 1-true | 1 if "Real Size" screenshot exists   |
| screenshots list        | list                 | the list of all screenshots of this template separated by <delimiter>, started with <list_begin> and ended with <list_end>. Full URL is displayed. |
| keywords list           | list                 | a list of all keywords associated with the template separated by<delimiter> starting   |



| Column                        | Type   | Description   |
|-------------------------------|--------|---|
|                               |        | with <list_begin> and ending with <list_end>.   |
| categories list (Identifiers) | list   | a list of all category identifiers of this template separated by <delimiter> starting with <list_begin> and ending with <list_end>.   |
| categories list (names)       | list   | a list of all category names of this template separated by <delimiter> starting with <list_begin> and ending with <list_end>.   |
| sources                       | string | information about sources available for this template starting with <list_begin> and ending with <list_end>.  |
| type                          | string | a type of the template starting with <list_begin> and ending with <list_end>.   |
| description                   | string | a description of this template starting with <list_begin> and ending with <list_end>.   |
| pages                         | list   | a list of all pages of this template starting with <list_begin> and ending with <list_end>. Each page consists of the page name (starting with <list_begin> and ending with <list_end>) and the list of screenshots (starting with <list_begin> and ending with <list_end>). Each screenshot consists of the screenshot name (starting with <list_begin> and ending with <list_end>) and the screenshot URL (starting with <list_begin> and ending with <list_end>). Full URL is displayed. |

**Response example:**

[http://www.templatemonster.com/webapi/template\\_info3.php?delim=&template\\_number=9005&list\\_delim=&list\\_begin=&list\\_end=](http://www.templatemonster.com/webapi/template_info3.php?delim=&template_number=9005&list_delim=&list_begin=&list_end=)

9005|174|6960|2005-08-11|6|0|0|0|0|0|0|150|Monet|0|1|[http://images.templatemonster.com/screenshots/9000/9005-banner.jpg; http://images.templatemonster.com/screenshots/9000/9005-html.html;http://images.templatemonster.com/screenshots/9000/9005-m.jpg; http://images.templatemonster.com/screenshots/9000/9005-osc-b.jpg; http://images.templatemonster.com/screenshots/9000/9005-rs.jpg]] [shop;hardware;accessory;broadband;laptop;notebook;changer;stereo;system;player;computer;camera;phone;mobile;CD-RW;desktop;printer;Xerox;HP;monitor;barebone;mice;input;device;memory;server;wireless;MP3;player]] [42;50;63;83;84][[Online store/shop;Electronics;Clean style;Most Popular;osCommerce Templates]] [.PSD; .PHP][[OS commerce 2.2][[OsCommerce Templates are ready made solutions to use for on-line shops. OsCommerce Template is actually a combination of osCommerce 2.2 (ready made on-line shop) provided by osCommerce.com and the original osCommerce design. ]][[Homepage]] [[REAL SIZE SCREENSHOT][http://images.templatemonster.com/screenshots/9000/9005-rs.jpg]] [[http://images.templatemonster.com/screenshots/9000/9005-html.html]] [[OSCommerce Main Page preview][http://images.templatemonster.com/screenshots/9000/9005-osc-b.jpg]]]]

**1.11. currency.php**

**URL:**

<http://www.templatemonster.com/webapi/currency.php>

**Description:**

Returns a table of currency exchange rates.

**Status:**

0.1

**Synopsis:**

[http://www.templatemonster.com/webapi/currency.php?\[\[linebreak=<linebreak>\]\]\[&delim=<delimiter>\]](http://www.templatemonster.com/webapi/currency.php?[[linebreak=<linebreak>]][&delim=<delimiter>])

**Parameters:**

| Parameter | Type   | Description   |
|-----------|--------|---|
| linebreak | string | a sequence of characters used to separate the lines (default: <code>\r\n</code> ) |
| delim     | string | a sequence of characters used to separate the columns (default: <code>\t</code> ) |

**Response:**

Response is a plain text table delimited with `<delimiter>`. The table contains information about currency exchange rates. It consists of the following columns (without columns headers):

| Column                        | Type    |
|-------------------------------|---------|
| id of the currency            | integer |
| name of the currency          | string  |
| exchange rate of the currency | float   |

**Response example:**

<http://www.templatemonster.com/webapi/currency.php?delim=|>

```
1 | EUR | 0.882503
2 | CAD | 1.21932
3 | GBP | 0.609381
4 | JPY | 127.203
5 | AUD | 1.4079
```

## 2. Obtaining Screenshots.

Use a script `templates_screenshots4.php` to get the list of screenshots URLs for a particular template.

For example, we can obtain a list of screenshots for a template number 1000 using [http://www.templatemonster.com/webapi/templates\\_screenshots4.php?from=20000&to=20000](http://www.templatemonster.com/webapi/templates_screenshots4.php?from=20000&to=20000) Than we can add the variable part of the URL to `templatemonster.com` domain name and download the screenshot using an URL: <http://www.templatemonster.com/screenshots/20000/20000-m.jpg>

## 3. Checking an Order Status.

**URL:**

[http://www.templatemonster.com/webapi/order\\_status.php](http://www.templatemonster.com/webapi/order_status.php)

**Description:**

Returns the status of the requested order

**Status:**

0.1

**Synopsis:**

[http://www.templatemonster.com/webapi/order\\_status.php?order\\_id=<templatemonster\\_order\\_id>](http://www.templatemonster.com/webapi/order_status.php?order_id=<templatemonster_order_id>)

**Parameters:**

| Parameter                | Type                     | Description                      |
|--------------------------|--------------------------|----------------------------------|
| templatemonster_order_id | string( 20 chars length) | TemplateMonster order identifier |

**Response:**

Response is a string containing a single word which describes a current status of the requested order:

| Value   | Description  |
|---------|--|
| Attempt | an order has not been paid for yet                                     |
| Bought  | successful purchase  |
| Fraud   | transaction was cancelled  |
| Wrong   | there is no order associated with a specified order ID in the database |

**Response example:**

[http://www.templatemonster.com/webapi/order\\_status.php?order\\_id=7oyH4IMR78hxHaAv43hZ](http://www.templatemonster.com/webapi/order_status.php?order_id=7oyH4IMR78hxHaAv43hZ)

Fraud

## 4. XML API specification.

Download complete information about all templates in a single zipped XML file: [http://www.templatemonster.com/webapi/xml/t\\_info.zip](http://www.templatemonster.com/webapi/xml/t_info.zip)

### 4.1. t\_info.zip.

**URL::**

[http://www.templatemonster.com/webapi/xml/t\\_info.zip](http://www.templatemonster.com/webapi/xml/t_info.zip)

**Description:**

Download complete information about all templates in a single zipped XML file.

**Status:**

0.1

**Synopsis:**

[http://www.templatemonster.com/webapi/xml/t\\_info.zip](http://www.templatemonster.com/webapi/xml/t_info.zip)

**Parameters:**

No

**Response:**

XML file contains an XML-encoded array. The array consists of the following arrays:

| Field                  | Type                 | Description  |
|------------------------|----------------------|--|
| id                     | integer              | an item number of the template   |
| state                  | integer              | equals 0 for hidden templates. Equals 1 for visible templates. Equals 2 for exclusively sold templates.  |
| price                  | integer              | a regular price of the template (in USD)   |
| exc_price              | integer              | an exclusive price of the template (in USD)  |
| inserted_date          | date                 | date of addition in YYYY-MM-DD format  |
| downloads              | integer              | the number of downloads  |
| template_type          | string               | a type of the template   |
| update_date            | date                 | The date of the latest update in the format YYYY-MM-DD hh:mm:ss  |
| is_flash               | integer (1/0) 1-true | 1 for Flash Intro templates  |
| is_adult               | integer (1/0) 1-true | 1 for Adult templates  |
| <width>980px</width>   |                      | Width of the template in pixels  |
| sources_available_list | array                | The list of IDs corresponding to the node<br><sources></sources><br>of the directories archive t_info_dir.zip. The list contains IDs of the source formats included into redistributable package of the template.  |
| screenshots_list       | array                | An array of all the screenshots and time of the screenshot modification. Full URL is displayed. Contains small_preview and main_preview arrays that have the 1 value for the screenshots of the small template preview and main template preview (the image showing on roll-over) accordingly. |
| software_required_list | array                | The list of IDs corresponding to the node<br><softwares></softwares><br>of the directories archive t_info_dir.zip. The list contains IDs of the software needed for editing and changing sources of the template.  |
| author                 | integer              | a template author  |
| is_full_site           | integer (1/0) 1-true | 1 for Full Site templates  |
| is_real_size           | integer (1/0) 1-true | 1 if a "Real Size" screenshot exists   |

| Field             | Type   | Description  |
|-------------------|--------|--|
| screenshots_list  | array  | an array of all screenshots and screenshots file modification time. Full URL is displayed.   |
| keywords          | string | a list of all keywords associated with a particular template (space separated).  |
| styles            | array  | an array of all styles of a particular template  |
| categories        | array  | an array of all categories of a particular template  |
| sources           | string | information about sources available for this template( deprecated).  |
| description       | string | a description of the template.   |
| software_required | string | a software required for editing the template (deprecated).   |
| pages             | array  | an array of all pages of the template. Each page consists of the name of the page and the list of screenshots. Each screenshot consists of the screenshot name and the URL. Full URL is displayed. |
| packages          | int    | The number of the package to which the template belongs.   |

**Response example:**

```
<?xml version="1.0" encoding="utf-8" ?>
<templates>
  <template id="21000">
    <id>21000</id>
    <state>1</state>
    <price>140</price>
    <exc_price>1100</exc_price>
    <inserted_date>2008-09-15 05:15:02</inserted_date>
    <update_date>2008-10-15 04:33:57</update_date>
    <downloads>0</downloads>
    <template_type>
      <type_id>16</type_id>
      <type_name>ZenCart Templates</type_name>
    </template_type>
    <is_flash>0</is_flash>
    <is_adult>0</is_adult>
    <width>766px</width>
    <author>
      <author_id>85</author_id>
      <author_nick>Delta</author_nick>
    </author>
    <package>
      <package_id>132</package_id>
    </package>
    <is_full_site>0</is_full_site>
    <is_real_size>1</is_real_size>
    <screenshots_list>
      <screenshot>
```

```

    <uri>http://images.templatemonster.com/screenshots/21000/21000-banner.jpg</uri>
    <filemtime>2008-08-28 08:08:20</filemtime>
</screenshot>
<screenshot>
    <uri>http://images.templatemonster.com/screenshots/21000/21000-m.jpg</uri>
    <filemtime>2008-08-28 08:08:20</filemtime>
    <small_preview>1</small_preview>
</screenshot>
<screenshot>
    <uri>http://images.templatemonster.com/screenshots/21000/21000-rs.jpg</uri>
    <filemtime>2008-08-28 08:08:20</filemtime>
</screenshot>
<screenshot>
    <uri>http://images.templatemonster.com/screenshots/21000/21000-z-b.jpg</uri>
    <filemtime>2008-08-28 08:08:20</filemtime>
    <main_preview>1</main_preview>
</screenshot>
<screenshot>
    <uri>http://images.templatemonster.com/screenshots/21000/21000-z-b.jpg</uri>
    <filemtime>2008-08-28 08:08:203</filemtime>
    <main_preview>1</main_preview>
</screenshot>
<screenshot>
    <uri>http://images.templatemonster.com/screenshots/21000/21000-z-html.html</uri>
    <filemtime>2008-08-28 08:08:20</filemtime>
</screenshot>
</screenshots_list>
<keywords>photo video store online shop camera products electronics portable monitor
<styles>
    <style>
        <style_id>16</style_id>
        <style_name>Neutral</style_name>
    </style>
</styles>
<categories>
    <category>
        <category_id>13</category_id>
        <category_name>Neutral</category_name>
    </category>
    <category>
        <category_id>40</category_id>
        <category_name>Art Photography</category_name>
    </category>
    <category>
        <category_id>42</category_id>
        <category_name>Online store/shop</category_name>
    </category>
    <category>
        <category_id>50</category_id>
        <category_name>Electronics</category_name>
    </category>
    <category>
        <category_id>78</category_id>
        <category_name>Zero Downloads</category_name>
    </category>
    <category>
        <category_id>110</category_id>
        <category_name>Zen cart Templates</category_name>
    </category>

```

```
</categories>
<sources_available_list>
  <source>
    <source_id>3</source_id>
  </source>
  <source>
    <source_id>12</source_id>
  </source>
</sources_available_list>
<sources>.PSD; &lt;br&gt; .PHP;</sources>
<description></description>
<software_required_list>
  <software>
    <software_id>29</software_id>
  </software>
  <software>
    <software_id>30</software_id>
  </software>
  <software>
    <software_id>64</software_id>
  </software>
  <software>
    <software_id>8</software_id>
  </software>
  <software>
    <software_id>26</software_id>
  </software>
  <software>
    <software_id>53</software_id>
  </software>
</software_required_list>
<software_required>PHP 4.3.2 or higher (PHP 4.4.x for optimal performance); Apache 1.3.
<pages>
  <page>
    <name>Main</name>
    <screenshots>
      <scr>
        <description>REAL SIZE SCREENSHOT</description>
        <uri>http://images.templatemonster.com/screenshots/21000/21000-rs.jpg</uri>
        <scr_type_id>0</scr_type_id>
        <width>0</width>
        <height>0</height>
        <href></href>
      </scr>
      <scr>
        <description/>
        <uri>http://images.templatemonster.com/screenshots/21000/21000-z-html.html</uri>
        <scr_type_id>127</scr_type_id>
        <width>430</width>
        <height>60</height>
        <href></href>
      </scr>
      <scr>
        <description>Zen-cart Main page preview</description>
        <uri>http://images.templatemonster.com/screenshots/21000/21000-z-b.jpg</uri>
        <scr_type_id>122</scr_type_id>
        <width>430</width>
        <height>586</height>
        <href></href>
      </scr>
    </screenshots>
  </page>
</pages>
```

```

    </scr>
  </screenshots>
</page>
</pages>
</template>
</templates>

```

## 4.2. template\_updates.php.

The script allows to download complete information about templates that were updated during a certain period.

### URL:

[http://www.templatemonster.com/webapi/template\\_updates.php](http://www.templatemonster.com/webapi/template_updates.php)

### Description:

Returns XML with information about templates that were updated during a certain period.

### Status:

0.1

### Synopsis:

[http://www.templatemonster.com/webapi/template\\_updates.php?from=<from\\_date\\_time>&to=<to\\_date\\_time>](http://www.templatemonster.com/webapi/template_updates.php?from=<from_date_time>&to=<to_date_time>)

### Parameters:

| Parameter | Type                           | Description                                 |
|-----------|--------------------------------|---|
| from      | date & time (19 chars length)  | Date & time in "YYYY-MM-DD hh:mm:ss" format |
| to        | date & time ( 19 chars length) | Date & time in "YYYY-MM-DD hh:mm:ss" format |

### Response:

XML file contains an XML-encoded array. The array consists of the following arrays:

| Field         | Type                 | Description   |
|---------------|----------------------|---|
| id            | integer              | an item number of the template  |
| state         | integer              | equals 0 for hidden templates. Equals 1 for visible templates. Equals 2 for exclusively sold templates. |
| price         | integer              | a regular price of the template (in USD)  |
| exc_price     | integer              | an exclusive price of the template (in USD)   |
| inserted_date | date                 | date of addition in YYYY-MM-DD format   |
| downloads     | integer              | the number of downloads   |
| template_type | string               | a type of the template  |
| update_date   | date                 | The date of the latest update in the format YYYY-MM-DD hh:mm:ss   |
| is_flash      | integer (1/0) 1-true | 1 for Flash Intro templates   |
| is_adult      | integer (1/0) 1-true | 1 for Adult templates   |



| Field                  | Type                 | Description  |
|------------------------|----------------------|--|
| <width>980px</width>   |                      | Width of the template in pixels  |
| sources_available_list | array                | The list of IDs corresponding to the node<br><sources></sources><br>of the directories archive t_info_dir.zip. The list contains IDs of the source formats included into redistributable package of the template.  |
| screenshots_list       | array                | An array of all the screenshots and time of the screenshot modification. Full URL is displayed. Contains small_preview and main_preview arrays that have the 1 value for the screenshots of the small template preview and main template preview (the image showing on roll-over) accordingly. |
| software_required_list | array                | The list of IDs corresponding to the node<br><softwares></softwares><br>of the directories archive t_info_dir.zip. The list contains IDs of the software needed for editing and changing sources of the template.  |
| author                 | integer              | a template author  |
| packages               | int                  | The number of the package to which the template belongs.   |
| is_full_site           | integer (1/0) 1-true | 1 for Full Site templates  |
| is_real_size           | integer (1/0) 1-true | 1 if a "Real Size" screenshot exists   |
| screenshots_list       | array                | an array of all screenshots and screenshots file modification time. Full URL is displayed.   |
| keywords               | string               | a list of all keywords associated with a particular template (space separated).  |
| styles                 | array                | an array of all styles of a particular template  |
| categories             | array                | an array of all categories of a particular template  |
| sources                | string               | information about sources available for this template( deprecated).  |
| description            | string               | a description of the template.   |
| software_required      | string               | a software required for editing the template (deprecated).   |
| pages                  | array                | an array of all pages of the template. Each page consists of the name of the page and the list of screenshots. Each screenshot consists of the screenshot name and the URL. Full URL is displayed.   |

**Response example:**

[http://www.templatemonster.com/webapi/template\\_updates.php?from=2005-07-16%2022:00:00&to=2005-07-17%2000:00:00](http://www.templatemonster.com/webapi/template_updates.php?from=2005-07-16%2022:00:00&to=2005-07-17%2000:00:00)

**4.3. template\_xml.php.**

Receive full template info in xml format by the template number.

**URL:**

[http://www.templatemonster.com/webapi/template\\_xml.php](http://www.templatemonster.com/webapi/template_xml.php)

**Description:**

Returns xml with the info about the requested template- template\_number.

**Synopsis:**

[http://www.templatemonster.com/webapi/template\\_xml.php?template\\_number=<template\\_number>](http://www.templatemonster.com/webapi/template_xml.php?template_number=<template_number>)

**Parameters:**

| Parameter       | Type    | Description     |
|-----------------|---------|-----------------|
| template_number | integer | Template number |

**Response:**

XML file contains an XML-encoded array. The response format is similar to template\_updates.php and t\_info.xml.

**4.4. t\_info\_dir.zip.**

Directories Archive.

**URL:**

[http://www.templatemonster.com/webapi/xml/t\\_info\\_dir.zip](http://www.templatemonster.com/webapi/xml/t_info_dir.zip)

**Description:**

Download full info about directories in XML format. Contains sources, softwares, categories and authors notes packed into .zip archive.

**Synopsis:**

[http://www.templatemonster.com/webapi/xml/t\\_info\\_dir.zip](http://www.templatemonster.com/webapi/xml/t_info_dir.zip)

**Parameters:**

No

**Response:**

| Field      | Type  | Description  |
|------------|-------|--|
| sources    | array | List of sources included with the template, value-name pairs format.           |
| softwares  | array | List of software required for template customization, value-name pairs format. |
| categories | array | List of template categories, value-name pairs format.                          |

| Field    | Type  | Description   |
|----------|-------|---|
| authors  | array | List of the template authors, value-name pairs format.                  |
| packages | array | List of the packages that templates belong to, value-name pairs format. |

**Response example:**

[http://www.templatemonster.com/webapi/template\\_updates.php?from=2005-07-16%2022:00:00&to=2005-07-17%2000:00:00](http://www.templatemonster.com/webapi/template_updates.php?from=2005-07-16%2022:00:00&to=2005-07-17%2000:00:00)

```
<?xml version="1.0" encoding="utf-8"?>
  <directories>
    <sources>
      <source>
        <id>2</id>
        <name> .HTML</name>
      </source>
    </sources>
    <softwares>
      <software>
        <id>8</id>
        <name> Adobe Photoshop CS+</name>
      </software>
    </softwares>
    <categories>
      <category>
        <id>1</id>
        <name>Beauty</name>
      </category>
    </categories>
    <authors>
      <author>
        <id>135</id>
        <name>Adonis</name>
      </author>
    </authors>
    <packages>
      <package>
        <id>141</id>
        <name>WordPress 2.6</name>
      </package>
    </packages>
  </directories>
```

---

# Chapter 3. Versions History

## 2005/08/04

- *styles.php* script was added
- *template\_styles.php* script was added
- *currency.php* script was added

## 2006/06/25

- *template\_xml.php* script was added
- *t\_info\_dir.zip* was added
- *template\_updates.php* script was updated
- *t\_info.zip* was updated

## 2004/09/29

- *locales* parameter was added to *categories.php* script
- *currency* parameter was added to *templates\_screenshots4.php* script

## 2004/07/12

- XML API was updated

## 2004/05/07

- *templates\_updates.php* script was added
- *xml/t\_info.zip* was added

## 2004/04/07

- *template\_info.php* script was added

## 2003/12/29

- *templates\_screenshots4.php* script was added
- *templates\_screenshots3.php* script was deprecated

## 2003/08/28

- *templates\_screenshots3.php* script was added
- *templates\_screenshots2.php* script was deprecated

## 2003/05/29

- *templates\_screenshots2.php* script was added
- *templates.php* and *templates\_screenshots.php* scripts were deprecated

## 2003/04/17

- *featured.php* script was added

## 2003/04/16

- *templates.php* - new parameter *category*
- *templates.php* - new parameter *sort\_by*
- *templates.php* - new parameter *order*
- *templates\_screenshots.php* script was added

**2003/04/15**

- *templates.php* - new parameter *filter*

---

# Chapter 4. Appendix.

## 1. Useful Links.

<http://www.template-help.com/> - Unbranded Help Center

<http://www.template-help.com/kb> - Knowledgebase

<http://www.template-help.com/tickets> - Submit a Support Ticket

<http://www.template-help.com/samples> - Sample Templates

<http://www.template-help.com/library> - Clipart Library

<http://www.template-help.com/chat> - Support Chat

## 2. Links to the Shopping Cart

**URL:** <http://www.templatehelp.com/preset/cart.php>

**Description:** A shopping cart script. You should use parameters specified in the synopsis for <http://www.templatehelp.com/preset/cart.php> to let your visitors select and purchase templates, review what they have selected, make necessary modifications or additions to their shopping carts. You should create a preset in the Mytemplatestorage.com affiliate account to get a unique preset identifier (code). Refer to Mytemplatestorage.com User Guide for more detailed information on how to create and manage presets.

**Synopsis:** [http://www.templatehelp.com/preset/cart.php?pr\\_code=<pr\\_code>&act=<action>&templ=<template\\_number1>%20<template\\_number2>%20<template\\_number3>](http://www.templatehelp.com/preset/cart.php?pr_code=<pr_code>&act=<action>&templ=<template_number1>%20<template_number2>%20<template_number3>)

### Parameters:

| Parameter | Type                             | Description  |
|-----------|----------------------------------|--|
| pr_code   | string (30 chars length)         | Your MyTemplateStorage preset identifier   |
| act       | string                           | A parameter that allows to manage a shopping cart. Acceptable values: <ul style="list-style-type: none"><li>• <i>add</i> - to add a particular template to the shopping cart</li><li>• <i>empty</i> - to empty the shopping cart (delete all items from the shopping cart)</li><li>• <i>del</i> - to delete a particular item (template) from the shopping cart.</li></ul> |
| templ     | list of space separated integers | item number(s) of the template   |

**Example:** To add a template #9000 to the shopping cart you need to use the following script URL: [http://www.templatehelp.com/preset/cart.php?pr\\_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=add&templ=9000](http://www.templatehelp.com/preset/cart.php?pr_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=add&templ=9000)

To delete a template #9000 from the shopping cart you need to use the following script URL: [http://www.templatehelp.com/preset/cart.php?pr\\_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=del&templ=9000](http://www.templatehelp.com/preset/cart.php?pr_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=del&templ=9000)

To empty a shopping cart (delete all items from the shopping cart) you need to use the following script URL: [http://www.templatehelp.com/preset/cart.php?pr\\_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=empty](http://www.templatehelp.com/preset/cart.php?pr_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=empty)

To add several templates (#8541, 9632, 1, 4555, and 8523) to the shopping cart you need to use the following script URL:

```
http://www.templatehelp.com/preset/cart.php?  
pr_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=add&templ=8541%209632%201%204555%208523
```

To delete several templates (#8541, 9632) from the shopping cart you need to use the following script URL:

```
http://www.templatehelp.com/preset/cart.php?  
pr_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=del&templ=8541%209632
```

where xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx is your unique preset identifier (code).

## 3. Links to Templatetuning.com

If you wish to include a link to Templatetuning.com at your template shop use the following URL to let your visitors navigate to the main page of Templatetuning.com - [http://www.template-help.com/tuning/tuning.php?aff=<affiliate\\_username>](http://www.template-help.com/tuning/tuning.php?aff=<affiliate_username>)

or the following URL to let your visitors navigate to the registration page with a particular template selected - [http://www.template-help.com/tuning/tuning.php?aff=<affiliate\\_username>&t\\_number=<template\\_number>](http://www.template-help.com/tuning/tuning.php?aff=<affiliate_username>&t_number=<template_number>)

where '[affiliate\\_username](#)' is your affiliate username; '[template\\_number](#)' is an item number of the template.

# Glossary

## Glossary

|            |   |
|------------|---|
| API        | Historically, "application programming interface". Practically, an API is any interface that enables one program to use facilities provided by another, whether by calling that program, or by being called by it. At a higher level still, an API is a set of functionality delivered by a programming system, and as such the mix of APIs in a particular system tells you what that system can do. <a href="http://en.wikipedia.org/wiki/API">http://en.wikipedia.org/wiki/API</a> |
| ASP        | A server-side technology developed by Microsoft [ <a href="http://www.microsoft.com/">http://www.microsoft.com/</a> ] for dynamically-generated web pages that is marketed as an add-on to Internet Information Services (IIS [ <a href="http://www.microsoft.com/WindowsServer2003/iis/default.msp">http://www.microsoft.com/WindowsServer2003/iis/default.msp</a> ]). <a href="http://www.asp.net">www.asp.net</a> [ <a href="http://www.asp.net/">http://www.asp.net/</a> ]        |
| Coldfusion | A tag-based, middleware programming language used chiefly for writing web-based applications. <a href="http://www.macromedia.com/software/coldfusion">www.macromedia.com/software/coldfusion</a> [ <a href="http://www.macromedia.com/software/coldfusion/">http://www.macromedia.com/software/coldfusion/</a> ]  |
| database   | A collection of information stored in a computer in a systematic way, such that a computer program can consult it to answer questions.  |
| delimiter  | A sequence of characters used to separate the columns.  |
| float      | A type of data for storing numbers with decimal digits.   |
| HTTP       | Hyper Text Transfer Protocol; the World Wide Web protocol that performs the request and retrieve functions of a server. Commonly seen as the first part of a website address. <a href="http://www.w3.org/Protocols">www.w3.org/Protocols</a> [ <a href="http://www.w3.org/Protocols/">http://www.w3.org/Protocols/</a> ]  |
| integer    | A positive, negative or equal to zero number without a fractional part.   |
| linebreak  | A sequence of characters used to separate the lines.  |

|                 |   |
|-----------------|---|
| Perl            | Practical Extraction and Reporting Language is an open source server side programming language extensively used for web scripts and to process data passed via the Common Gateway Interface from HTML forms etc. Perl scripts are not embedded within HTML [ <a href="http://www.w3.org/MarkUp/">http://www.w3.org/MarkUp/</a> ] pages and do not download to the web browser but reside on the server. <a href="http://www.perl.com">www.perl.com</a> [ <a href="http://www.perl.com/">http://www.perl.com/</a> ]  |
| PHP             | Hypertext Preprocessor; an open source, server-side HTML [ <a href="http://www.w3.org/MarkUp/">http://www.w3.org/MarkUp/</a> ] scripting language used to create dynamic Web pages. PHP is embedded within tags, so the author can move between HTML and PHP instead of using large amounts of code. Because PHP is executed on the server, the viewer cannot see the code. PHP can perform the same tasks as a CGI [ <a href="http://hohoo.ncsa.uiuc.edu/cgi/">http://hohoo.ncsa.uiuc.edu/cgi/</a> ] program can do and is compatible with many different kinds of databases. <a href="http://www.php.net">www.php.net</a> [ <a href="http://www.php.net/">http://www.php.net/</a> ] |
| plain text      | Text encoded in the ASCII [ <a href="http://en.wikipedia.org/wiki/ASCII">http://en.wikipedia.org/wiki/ASCII</a> ] format. As such, it is software independent and can be imported, read, and exported by virtually every software application.  |
| protocol        | On the Internet "protocol" usually refers to a set of rules that define an exact format for communication between systems. For example the HTTP protocol defines the format for communication between web browsers and web servers, the IMAP [ <a href="http://www.imap.org/">http://www.imap.org/</a> ] protocol defines the format for communication between IMAP email servers and clients, and the SSL [ <a href="http://www.openssl.org/">http://www.openssl.org/</a> ] protocol defines a format for encrypted communications over the Internet.  |
| script          | A set of commands written in an interpreted language to automate certain application tasks.   |
| script response | Message of script that is returned to a sender.   |
| shopping cart   | A piece of software that acts as an online store's catalog and ordering process. Typically, a shopping cart is the interface between a company's Web site and its deeper infrastructure, allowing consumers to select merchandise; review what they have selected; make necessary modifications or additions; and purchase the merchandise.   |
| string          | A linear sequence of symbols (characters or words or phrases).  |
| synopsis        | A wrapper for command or function syntax.   |
| WebAPI          | An analog of the API for websites.  |
| XML             | Extensible Markup Language; a standard for creating markup languages which describe the structure of data. It is not a fixed set of elements like HTML [ <a href="http://www.w3.org/MarkUp/">http://www.w3.org/MarkUp/</a> ], but rather, it is like SGML [ <a href="http://www.w3.org/MarkUp/SGML/">http://www.w3.org/MarkUp/SGML/</a> ] (Standard Generalized Markup Language) in that it is a metalanguage, or a language for describing languages. XML enables authors to define their own tags. <a href="http://www.w3.org/XML">www.w3.org/XML</a> [ <a href="http://www.w3.org/XML/">http://www.w3.org/XML/</a> ]   |